

# SPECIFICATION

Attorney Docket No. 0638MH-40982-US

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN that I, **Gregory G. Kuelbs**, residing in the city of Westlake, Texas, have invented new and useful improvements in a

## UMBRELLA APPARATUS

of which the following is a specification.

"EXPRESS MAIL" No. EV024943769US
Date of Deposit: <u>2/7/02</u>
I hereby certify that this paper or fee is being deposited with the United States Postal Service Express Mail "Post Office to Addressee" service under 37 C.F.R. §1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box: Patent Application, P.O. Box 2327, Arlington, VA 22202-0327,  by <u>Jana E. Walke</u>

1 This application claims the benefit of U.S. Provisional Application No. 60/267,018,  
2 filed 7 February 2001, titled "Lighted Patio Umbrella Apparatus;" and of U.S. Provisional  
3 Application No. 60/335,933, filed 2 November 2001, titled "Outdoor Lighting Systems with  
4 Cold Cathode Tubes."

## 5 BACKGROUND OF THE INVENTION

### 6 1. Field of the Invention:

7 The present invention relates in general to patio umbrellas, and in particular, to an  
8 improved patio umbrella with integral lighting system and other modular electronic systems  
9 and components.

### 10 2. Description of the Prior Art:

11 There has been a recent increase in the interest in entertaining in a lawn and  
12 garden environment. Patio furniture is quite popular and useful for outdoor entertaining,  
13 especially in portions of the country that have warmer climates. However, the sun often  
14 presents an impediment to such outdoor entertaining. Consequently, sales have increased  
15 for relatively large patio and table umbrellas for use in shielding or shading table areas and  
16 people sitting around the tables from direct exposure to the sunlight. Given the relatively  
17 high degree of interest in patio umbrellas, it is likely that improved umbrellas, or umbrellas  
18 with enhanced functions, will be well received in the marketplace.

## SUMMARY OF THE INVENTION

It is one objective of the present invention to provide a lawn or patio umbrella with an integral lighting system that utilizes cold cathode tubes, light emitting diodes (LED's), or florescent lights, to provide relatively bright outdoor light for reading and other activities that require relatively high light intensities.

It is another objective of the present invention to provide an a lawn or patio umbrella with an integral lighting system that utilizes cold cathode tubes, LED's, or florescent lights, to provide relatively bright outdoor light, and its own rechargeable power supply, including solar cells.

It is yet another objective of the present invention to provide a lawn or patio umbrella with an integral lighting system that utilizes cold cathode tubes, LED's, or florescent lights, to provide relatively bright outdoor light, and a motorized retraction system that aids in opening and closing the umbrella.

It is yet another objective of the present invention to provide a lawn or patio umbrella with an integral lighting system that utilizes cold cathode tubes, LED's, or florescent lights, to provide relatively bright outdoor light, and a cooling system, such as one that utilizes electric fans or misting systems.

It is yet another objective of the present invention to provide a modular, electrically powered lawn or patio umbrella in which lighting systems, such as those utilizing cold cathode tubes, LED's, or florescent lights; cooling systems, such as those utilizing electric fans or misting systems; and motorized retraction systems; can be selectively interchanged.

The above objects are achieved, for example, by integrating a rechargeable power system, a lighting system, a motorized retraction system, and/or a cooling system into a relatively large patio umbrella. The resulting umbrella does not have to be connected to a household electrical system, is a relatively low power consuming device, does not generate much heat, provides a high amount of light intensity, reduces the overall energy consumption of outdoor lighting, allows for fewer batteries to be utilized in each lighting

1 fixture, allows for easier recharging of the batteries due to the lower power requirements,  
2 and allows the utilization of smaller photovoltaic solar cells.

3 In the embodiment that utilizes a cold cathode tube, one additional advantage is that  
4 the cold cathode tube may be operated at multiple voltage levels to provide differing  
5 amounts of light output. In one particular embodiment, a wireless receiver and transmitter  
6 pair may be utilized to allow an operator to use a wireless command signal to change the  
7 operating state of the lighting system, such as switching the system between an on and off  
8 condition, and switching the system between varying levels of light output. Accordingly, an  
9 operator may intensify the light output from the lighting system through use of a wireless  
10 handheld transmitter when he wants additional light from a particular umbrella.

11

12

## BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. However, the invention itself, as well as a preferred mode of use and further objectives and advantages thereof, will best be understood by reference to the following detailed description of the preferred embodiment when read in conjunction with the following drawings.

Figure 1 is a fragmentary and sectional view of the preferred embodiment of the lighted umbrella with motorized opening and closing system according to the present invention.

Figures 2A, 2B, and 2C are pictorial, fragmentary, and section views of an alternate embodiment of the present invention which is directed to a lighted umbrella with a stand and a single battery and removable base cover.

Figures 3A, 3B, and 3C are pictorial, fragmentary, and partial section views of another alternate embodiment of the present invention which is directed to a lighted umbrella with a stand, charger, batteries, and removable battery cover.

Figure 4A is a fragmentary and sectional view of another alternate embodiment of the present invention which is directed to a lighted umbrella with recessed lighting.

Figure 4B is a fragmentary and sectional view of another alternate embodiment of the present invention which is directed to a lighted umbrella with integral misting system.

Figure 4C is a fragmentary and sectional view of another alternate embodiment of the present invention which is directed to a lighted umbrella with an integral fan system.

Figure 5A is a block diagram representation of the motorized opening and closing system of the umbrella of Figure 1 and of the other embodiments of the umbrella of the present invention.

Figure 5B is a block diagram representation of an alternate embodiment of the motorized opening and closing system of Figure 5A.

1           Figure 6 is a simplified schematic of an alternative embodiment of the present  
2 invention which is directed to a lighted umbrella with a top-mounted power unit and a cold  
3 cathode tube lighting system.

4           Figure 7 is a simplified schematic of an alternative embodiment of the present  
5 invention which is directed to an umbrella with a top-mounted power unit and an electric  
6 fan cooling system.

7           Figure 8 is a simplified view of an alternative embodiment of the present invention  
8 which is directed to an umbrella with a top-mounted power unit and a mist producing  
9 cooling system.

10          Figure 9 is a simplified schematic of an alternate embodiment of the present  
11 invention that is directed to an umbrella with a top-mounted power unit and a motorized  
12 opening and closing system.

13          Figure 10 is a schematic of one broad implementation of the present invention.

14          Figure 11 is a block diagram representation of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

Referring to Figure 1 in the drawings, one embodiment of an umbrella apparatus according to the present invention is illustrated. Umbrella apparatus 11 includes an umbrella portion 13 and a hollow tubular pole portion 15. Pole portion 15 is coupled to and supports umbrella portion 13. Umbrella portion 13 is preferably retractable and may be moved between a raised, or expanded open position, which is shown; and a lowered, or retracted, closed position in which umbrella portion is collapsed down about pole portion 15, as is conventional. A flexible canopy 17 is attached to and covers umbrella portion 15. Canopy 17 is supported by a plurality of rib members 19, 21, 23, and 25. Rib members 19, 21, 23, and 25 are preferably hingedly coupled to pole portion 15 at an upper portion of pole portion 15. An integral lighting system 26 is carried by at least one of rib members 19, 21, 23, or 25. Lighting system 26 provides high intensity light to umbrella apparatus 11 and the surrounding area. In the embodiment of Figure 1, lighting system 26 preferably utilizes a cold cathode tube which will be described in greater detail herein.

Umbrella apparatus 11 may include a base member adapted to receive pole portion 15 and to support umbrella apparatus 11 in a generally upright position. Although not shown in the embodiment Figure 1, other embodiments of the present invention depict a variety of conventional and novel base members, any of which may be utilized with the embodiment of Figure 1. It should be understood that in all of the embodiments of the present invention discussed herein, umbrella apparatus 11 may be used with little or no base member whatsoever, provided there is a table or some other support structure, including the ground, which may be adapted to receive pole portion 15. For example, many patio tables are designed with central apertures to receive, support, and stabilize relatively large umbrellas. In some cases, the patio tables eliminate the need for a base member all together.

In accordance with the preferred embodiment of the present invention, light system 26 includes a plurality of light strands 27, 29, 31, and 33 attached to rib members 19, 21, 23, and 25. Each light strand 27, 29, 31, and 33 includes electrical

1 wiring 39 which conductively connects a plurality of small cold cathode tube light bulbs  
2 together for providing the high intensity light under canopy 17 and in the area  
3 surrounding umbrella apparatus 11. A wiring ring 37 secures and locates electrical  
4 wiring 39 of light strands 27, 29, 31, and 33, so that electrical wiring 39 may be passed  
5 through the hollow interior of pole portion 15 to a power source, as will be described in  
6 detail below.

7 Umbrella apparatus 11 includes an optional opening and closing system 40 that  
8 aids in expanding umbrella portion 13 into the open condition and retracting umbrella  
9 portion 13 into the closed condition. Opening and closing system 40 includes a cable  
10 system 41, a gear and pulley system 43 housed in a crank case 44, and a manual crank  
11 45. Crank case 44 is preferably located on pole portion 15 such that crank case 44 is  
12 accessible when umbrella portion 13 is in the fully retracted position against pole portion  
13 15. Cable system 41 is coupled between rib members 19, 21, 23, and 25 and gear and  
14 pulley system 43, and is preferably disposed within the hollow interior of pole portion 15.  
15 Manual crank 45 is coupled to gear and pulley system 43 so as to allow manual  
16 opening and closing of umbrella portion 13.

17 Opening and closing system 40 may be automated by the inclusion of an electric  
18 screw driver motor 49, or other similar relatively small diameter motor assembly, and  
19 one or more operational switches 47. Motor 49 is preferably disposed within the hollow  
20 interior of pole portion 15 and is coupled to gear and pulley system 43. Operational  
21 switches 47 are preferably carried by crank case 44, and include one or more switches  
22 for controlling the operation of motor 49. With the inclusion of motor 49, a user may  
23 expand and retract umbrella portion 13 simply by pressing the appropriate operational  
24 switch 47. This feature is particularly advantageous when used with large umbrellas  
25 which may be relatively heavy and awkward to operate, or when the user lacks  
26 sufficient strength to expand or retract umbrella portion 13.

27 Umbrella apparatus 11 includes a power system 50 having a power source 55.  
28 In this embodiment, power source 55 is preferably disposed in the hollow interior of pole  
29 portion 15 at a lower extremity and comprises one or more rechargeable batteries 55a.



1 A releasable end cap 57 having integral ground connectors is provided at the lowermost  
2 portion of pole portion 15 to complete the electrical circuit of power system 50 and to  
3 allow access to rechargeable batteries 55a, as rechargeable batteries 55a may have to  
4 be periodically replaced. Power system 50 provides electrical power to lighting system  
5 26 and opening and closing system 40. An external power system charger 51 is  
6 electrically coupled to power system 50 to aid in repeatedly charging rechargeable  
7 batteries 55a. As is shown in Figure 1, an external adapter 60 may be provided.  
8 External adapter 60 includes a relatively small plug 59 that is adapted to be conductively  
9 received by external power system charger 51, an extension cord 61, an electrical  
10 transformer 63, and terminals 65 that allow transformer 63 to be plugged into a  
11 conventional AC wall outlet. This allows power system charger 51 to receive power  
12 directly from a conventional AC wall outlet in order to recharge rechargeable batteries  
13 55a.

14 In accordance with a preferred embodiment of the present invention, an  
15 alternative power system charger 62 may be provided. Alternate power system charger  
16 62 includes at least one solar cell 35 carried by an upper cap portion 64. Solar cells 35  
17 are conductively coupled to power system charger 51 via wires (not shown) that pass  
18 through the hollow interior of pole portion 15, thereby allowing solar cells 35 to provide  
19 an electrical charge to recharge rechargeable batteries 55a, provided sunlight falls upon  
20 solar cells 35. Because solar cells 35 provide continuous recharging throughout the  
21 daylight hours, the amount and frequency of charging power system 50 with external  
22 power system charger 60 may be minimized. It is important to note that locating  
23 alternate power system charger 62 atop umbrella portion 13 is unique and  
24 advantageous, particularly when alternate power system charger 62 includes solar cells  
25 35 or other types of solar energy collectors. Such location limits the visibility of alternate  
26 power system charger 62 and ensures that solar energy collection is maximized.

27 The embodiment depicted in Figure 1 is advantageous over the prior art in that it  
28 provides a number of useful functions. Umbrella apparatus 11 is lighted by lighting  
29 system 26 which does not require continuous access to a conventional AC wall outlet,  
30 while providing high intensity light. This allows umbrella apparatus 11 to be placed in a

1 relatively remote lawn or garden locations that are away from, or substantially removed  
2 from, conventional AC power outlets. During daylight hours, solar cells 35 provide a  
3 continuous trickle charge to recharge rechargeable batteries 55a, thereby reducing the  
4 need for and frequency of use of external power system charger 60. However, when an  
5 electrical charge is needed, external power system charger 60 may be utilized to  
6 directly charge power system charger 51. Of course, a conventional extension cord  
7 may be used, thereby eliminating the need to move umbrella apparatus 11 from its  
8 remote location to a location near an AC power outlet.

9 Referring now to Figures 2A-2C in the drawings, another embodiment of the  
10 present invention is illustrated. In this embodiment, an umbrella apparatus 111 includes  
11 an umbrella portion 113, a pole portion 115, a stand portion 118, and a base portion 120  
12 adapted to house a rechargeable power system 151. Umbrella apparatus 11 includes a  
13 lighting system 126 and may include a motorized opening and closing system 140.  
14 Umbrella portion 113 is preferably retractable and may be moved between a raised, or  
15 expanded open position, which is shown; and a lowered, or retracted, closed position in  
16 which umbrella portion is collapsed down about pole portion 115, as is conventional. A  
17 flexible canopy 117 is attached to and covers umbrella portion 115. Canopy 117 is  
18 supported by a plurality of rib members 119, 121, 123, and 125. Rib members 119,  
19 121, 123, and 125 are preferably hingedly coupled to pole portion 115 at an upper  
20 portion of pole portion 115. An integral lighting system 126 is carried by at least one of  
21 rib members 119, 121, 123, or 125. Lighting system 126 provides high intensity light to  
22 umbrella apparatus 111 and the surrounding area. In the embodiment of Figures 2A-  
23 2C, lighting system 126 preferably utilizes a cold cathode tube which will be described in  
24 greater detail herein.

25 Lighting system 126 includes a plurality of light strands 127, 129, 131, and 133  
26 attached to rib members 119, 121, 123, and 125. Each light strand 127, 129, 131, and  
27 133 includes electrical wiring 139 which conductively couples a plurality of small cold  
28 cathode tube light bulbs together for providing the high intensity light under canopy 117  
29 and in the area surrounding umbrella apparatus 111. A wiring ring 137 secures and  
30 locates electrical wiring 139 of light strands 127, 129, 131, and 133, so that electrical

wiring 139 may be passed through the hollow interior of pole portion 115 to a power source, as will be described in detail below.

Umbrella apparatus 111 includes an optional opening and closing system 140 that aids in expanding umbrella portion 113 into the open condition and retracting umbrella portion 113 into the closed condition. Opening and closing system 140 includes a cable system 141, a gear and pulley system 143 housed in a crank case 144, and a manual crank 145. Crank case 144 is preferably located on pole portion 115 such that crank case 144 is accessible when umbrella portion 113 is in the fully retracted position against pole portion 115. Cable system 141 is coupled between rib members 119, 121, 123, and 125 and gear and pulley system 143, and is preferably disposed within the hollow interior of pole portion 115. Manual crank 145 is coupled to gear and pulley system 143 so as to allow manual opening and closing of umbrella portion 113.

Opening and closing system 140 may be automated by the inclusion of an electric screw driver motor 149, or other similar relatively small diameter motor assembly, and one or more operational switches 147. Motor 149 is preferably disposed within the hollow interior of pole portion 115 and is coupled to gear and pulley system 143. Operational switches 147 are preferably carried by crank case 144, and include one or more switches for controlling the operation of motor 149. With the inclusion of motor 149, a user may expand and retract umbrella portion 113 simply by pressing the appropriate operational switch 147. This feature is particularly advantageous when used with large umbrellas which may be relatively heavy and awkward to operate, or when the user lacks sufficient strength to expand or retract umbrella portion 113.

Umbrella apparatus 111 includes a power system 150 having a power source 155. In this embodiment, power source 155 is preferably adapted to be conductively coupled to base portion 120 and comprises a rechargeable battery pack 155a, preferably an 18-Volt rechargeable battery pack. Battery pack 155a is preferably the type of rechargeable battery that is utilized with most modern cordless power tools, such as drills, saws, and sanders. Battery pack 155a is adapted to be repeatedly

1 recharged by plugging battery pack 155a into a conventional charger (not shown) that is  
2 plugged into a conventional AC power outlet. Power system 150 provides electrical  
3 power to lighting system 126 and opening and closing system 140.

4 In accordance with a preferred embodiment of the present invention, an  
5 alternative power system charger 162 may be provided. Alternate power system  
6 charger 162 includes at least one solar cell 135 carried by an upper cap portion 164.  
7 Solar cells 135 are conductively coupled to power system 150 via wires (not shown) that  
8 pass through the hollow interior of pole portion 115, thereby allowing solar cells 135 to  
9 provide an electrical charge to recharge rechargeable battery pack 155a, provided  
10 sunlight falls upon solar cells 135. Because solar cells 135 provide continuous  
11 recharging throughout the daylight hours, the frequency with which battery pack 155a  
12 must be replaced or recharged may be minimized. It is important to note that locating  
13 alternate power system charger 162 atop umbrella portion 113 is unique and  
14 advantageous, particularly when alternate power system charger 162 includes solar  
15 cells 135 or other types of solar energy collectors. Such location limits the visibility of  
16 alternate power system charger 162 and ensures that solar energy collection is  
17 maximized.

18 Stand portion 118 includes an upright shaft portion 170 having a central aperture  
19 172 that is adapted to receive the pole portion 115 of umbrella apparatus 111. A  
20 plurality of screw clamps 174 and 176 are provided to secure pole portion 115 within  
21 shaft portion 170. A bottom portion 146 is provided to stabilize umbrella apparatus 111  
22 while umbrella apparatus 111 is installed within stand portion 118.

23 Base portion 120 includes a removable cylindrical sleeve 156, a removable cover  
24 160, and a receiver 168. Sleeve 156 is configured to slip over the exterior of shaft  
25 portion 170, and includes a longitudinal slot 158 that allows access to screw clamps 174  
26 and 176 when sleeve 156 is placed over shaft portion 170. Slot 158 also allows access  
27 to a connector 166 disposed in the lower portion of pole portion 115 when sleeve 156 is  
28 placed over shaft portion 170. Connector 166 is conductively coupled to the wires from  
29 alternate power system charger 162 and solar cells 135. Cover 160 is preferably

1 concave in shape, thereby defining an interior space which may be used to house the  
2 electronics (not shown) of power system 150. Cover 160 may include one or more  
3 seams 162 that allow access to the interior space defined by cover 160. Receiver 168  
4 releasably receives battery pack 155a. A wire 152 and plug 154 conductively couple  
5 battery pack 155a to connector 166, thereby providing an electrical circuit between  
6 rechargeable battery pack 155a and light strands 119, 121, 123, and 125 of lighting  
7 system 126.

8 The embodiment depicted in Figures 2A-2C is advantageous over the prior art in  
9 that it provides a number of useful functions. Umbrella apparatus 111 is lighted by  
10 lighting system 126 which does not require continuous access to a conventional AC wall  
11 outlet, while providing high intensity light. This allows umbrella apparatus 111 to be  
12 placed in a relatively remote lawn or garden locations that are away from, or  
13 substantially removed from, conventional AC power outlets. During daylight hours,  
14 solar cells 135 provide a continuous trickle charge to recharge rechargeable battery  
15 pack 155a, thereby reducing the frequency with which battery pack 155a must be  
16 replaced or recharged. Additionally, this embodiment is advantageous over the prior art  
17 in that conventional rechargeable battery packs, which are commonly used with  
18 cordless power tools, may be utilized. If battery pack 155a is insufficiently charged  
19 illuminate light strands 119, 121, 123, and 125 of light system 126, the user may simply  
20 replace battery pack 155a with another fully charged battery pack 155a. In this manner,  
21 lighting system 126 of umbrella apparatus 111 may be energized conveniently, even  
22 though umbrella apparatus 111 may be located extremely remotely from an AC power  
23 outlet, such as in a garden patio, or on a boat dock. In this embodiment, there is no  
24 need to use extension cords to charge an alternate power system charger.

25 Referring now to Figures 3A-3C in the drawings, another embodiment of the  
26 present invention is illustrated. In this embodiment, an umbrella apparatus 211 includes  
27 an umbrella portion 213, a pole portion 215, a stand portion 218, and a base portion 220  
28 adapted to house a rechargeable power system 251. Umbrella apparatus 211 includes  
29 a lighting system 226 and may include a motorized opening and closing system 240.  
30 Umbrella portion 213 is preferably retractable and may be moved between a raised, or

1 expanded open position, which is shown; and a lowered, or retracted, closed position in  
2 which umbrella portion is collapsed down about pole portion 215, as is conventional. A  
3 flexible canopy 217 is attached to and covers umbrella portion 215. Canopy 217 is  
4 supported by a plurality of rib members 219, 221, 223, and 225. Rib members 219,  
5 221, 223, and 225 are preferably hingedly coupled to pole portion 215 at an upper  
6 portion of pole portion 215. An integral lighting system 226 is carried by at least one of  
7 rib members 219, 221, 223, or 225. Lighting system 226 provides high intensity light to  
8 umbrella apparatus 211 and the surrounding area. In the embodiment of Figures 3A-  
9 3C, lighting system 226 preferably utilizes a cold cathode tube which will be described in  
10 greater detail herein.

11         Lighting system 226 includes a plurality of light strands 227, 229, 231, and 233  
12 attached to rib members 219, 221, 223, and 225. Each light strand 227, 229, 231, and  
13 233 includes electrical wiring 239 which conductively couples a plurality of small cold  
14 cathode tube light bulbs together for providing the high intensity light under canopy 217  
15 and in the area surrounding umbrella apparatus 211. A wiring ring 237 secures and  
16 locates electrical wiring 239 of light strands 227, 229, 231, and 233, so that electrical  
17 wiring 239 may be passed through the hollow interior of pole portion 215 to a power  
18 source, as will be described in detail below.

19         Umbrella apparatus 211 includes an optional opening and closing system 240  
20 that aids in expanding umbrella portion 213 into the open condition and retracting  
21 umbrella portion 213 into the closed condition. Opening and closing system 240  
22 includes a cable system 241, a gear and pulley system 243 housed in a crank case 244,  
23 and a manual crank 245. Crank case 244 is preferably located on pole portion 215  
24 such that crank case 244 is accessible when umbrella portion 213 is in the fully  
25 retracted position against pole portion 215. Cable system 241 is coupled between rib  
26 members 219, 221, 223, and 225 and gear and pulley system 243, and is preferably  
27 disposed within the hollow interior of pole portion 215. Manual crank 245 is coupled to  
28 gear and pulley system 243 so as to allow manual opening and closing of umbrella  
29 portion 213.

1        Opening and closing system 240 may be automated by the inclusion of an  
2 electric screw driver motor 249, or other similar relatively small diameter motor  
3 assembly, and one or more operational switches 247. Motor 249 is preferably disposed  
4 within the hollow interior of pole portion 215 and is coupled to gear and pulley system  
5 243. Operational switches 247 are preferably carried by crank case 244, and include  
6 one or more switches for controlling the operation of motor 249. With the inclusion of  
7 motor 249, a user may expand and retract umbrella portion 213 simply by pressing the  
8 appropriate operational switch 247. This feature is particularly advantageous when  
9 used with large umbrellas which may be relatively heavy and awkward to operate, or  
10 when the user lacks sufficient strength to expand or retract umbrella portion 213.

11        Umbrella apparatus 211 includes a power system 250 having a rechargeable  
12 power source 255. In this embodiment, power source 255 is preferably adapted to be  
13 conductively coupled to and housed within base portion 220 and comprises a bundle of  
14 rechargeable batteries 255a. Power system 250 provides electrical power to lighting  
15 system 226 and opening and closing system 240. An external power system charger  
16 and transformer 251 is electrically coupled to power system 250 to aid in repeatedly  
17 charging rechargeable batteries 255a. An extension cord 261 having terminals 265  
18 allow external power system charger and transformer 251 to be plugged into a  
19 conventional AC wall outlet. This allows external power system charger and  
20 transformer 251 to receive power directly from a conventional AC wall outlet in order to  
21 recharge rechargeable batteries 255a.

22        In accordance with a preferred embodiment of the present invention, an  
23 alternative power system charger 262 may be provided. Alternate power system  
24 charger 262 includes at least one solar cell 235 carried by an upper cap portion 264.  
25 Solar cells 235 are conductively coupled to power system 250 via wires (not shown) that  
26 pass through the hollow interior of pole portion 215, thereby allowing solar cells 235 to  
27 provide an electrical charge to recharge rechargeable batteries 255a, provided sunlight  
28 falls upon solar cells 235. Because solar cells 235 provide continuous recharging  
29 throughout the daylight hours, the frequency with which batteries 255a must be  
30 replaced or recharged may be minimized. It is important to note that locating alternate

1 power system charger 262 atop umbrella portion 213 is unique and advantageous,  
2 particularly when alternate power system charger 262 includes solar cells 235 or other  
3 types of solar energy collectors. Such location limits the visibility of alternate power  
4 system charger 262 and ensures that solar energy collection is maximized.

5 Stand portion 218 includes an upright shaft portion 270 having a central aperture  
6 272 that is adapted to receive pole portion 215 of umbrella apparatus 211. A plurality of  
7 screw clamps 274 and 276 are provided to secure pole portion 215 within shaft portion  
8 270. A bottom portion 246 is provided to stabilize umbrella apparatus 211 while  
9 umbrella apparatus 211 is installed within stand portion 218.

10 Base portion 220 includes a removable cylindrical sleeve 256, a removable cover  
11 260, and recessed portions 280 and 282. Sleeve 256 is configured to slip over the  
12 exterior of shaft portion 270, and includes a longitudinal slot 258 that allows access to  
13 screw clamps 274 and 276 when sleeve 256 is placed over shaft portion 270. Slot 258  
14 also allows access to a connector 266 disposed in the lower portion of pole portion 215  
15 when sleeve 256 is placed over shaft portion 270. Connector 266 is conductively  
16 coupled to the wires from alternate power system charger 262 and solar cells 235.  
17 Cover 260 is preferably concave in shape, thereby defining an interior space which may  
18 be used to house the electronics (not shown) of power system 250. Cover 260 may  
19 include one or more seams 262 that allow access to the interior space defined by cover  
20 260. Recessed portion 280 releasably receives batteries 255a, and recessed portion  
21 282 releasably receives external power system charger 251. A wire 252 and plug 254  
22 conductively couple batteries 255a to connector 266, thereby providing an electrical  
23 circuit between rechargeable batteries 255a and light strands 219, 221, 223, and 225 of  
24 lighting system 226.

25 The embodiment depicted in Figures 3A-3C is advantageous over the prior art in  
26 that it provides a number of useful functions. Umbrella apparatus 211 is lighted by  
27 lighting system 226 which does not require continuous access to a conventional AC wall  
28 outlet, while providing high intensity light. This allows umbrella apparatus 211 to be  
29 placed in a relatively remote lawn or garden locations that are away from, or



1 substantially removed from, conventional AC power outlets. During daylight hours,  
2 solar cells 235 provide a continuous trickle charge to recharge rechargeable batteries  
3 255a, thereby reducing the frequency with which batteries 255a must be replaced or  
4 recharged. However, when an electrical charge is needed, external power system  
5 charger 251 may be utilized to directly charge batteries 255a. Of course, a conventional  
6 extension cord may be used, thereby eliminating the need to move umbrella apparatus  
7 211 from its remote location to a location near an AC power outlet.

8 Referring now to Figure 4A in the drawings, the preferred embodiment of lighting  
9 systems 26, 126, and 226 of the present invention is illustrated. In this embodiment, a  
10 plurality of lighting elements 307, preferably cold cathode tube bulbs, are recessed into  
11 a rib member 301. Rib member 301 is indicative of rib members 19, 21, 23, 25, 119,  
12 121, 123, 125, 219, 221, 223, and 225. As is shown, a cavity 303 is formed within rib  
13 301. Cavity 303 is adapted to receive and hold light bulb 307. A translucent material  
14 305 extends along the entire length of the cavity 303 to protect bulbs 307 from damage  
15 and undesirable exposure to weather and other conditions. Translucent material 305  
16 may have a smooth surface or be textured to accentuate or enhance the light from  
17 bulbs 307. Although only a single cold cathode tube bulb 307 is illustrated, it should be  
18 understood that there may be many bulbs 307 spaced along the length of rib member  
19 301 to illuminate the area under umbrella apparatus 11, 111, or 211. Rib member 301  
20 includes a wiring channel 309 configured to receive a wire 311 that conductively  
21 connects all of the bulbs 307 installed in rib member 301, thereby forming an electrical  
22 circuit between bulbs 307 and the rechargeable power source, such as power sources  
23 50, 150, and 250. In this manner, recessed lighting, which is carried entirely within rib  
24 member 301 and is not otherwise exposed to the elements, is achieved.

25 Referring now to Figure 4B in the drawings, an alternate embodiment of lighting  
26 systems 26, 126, and 226 of the present invention is illustrated. This embodiment is  
27 similar to the embodiment of Figure 4A, with the exception that an integral cooling  
28 system 410 has been added. In this embodiment, a plurality of lighting elements 307,  
29 preferably cold cathode tube bulbs, are recessed into a rib member 301. Rib member  
30 301 is indicative of rib members 19, 21, 23, 25, 119, 121, 123, 125, 219, 221, 223, and

1 225. Cooling system 410 comprises a misting means that provides a light mist to cool  
2 the area under umbrella apparatus 11, 111, or 211. A cavity 403 is formed within rib  
3 member 401. Cavity 403 is adapted to receive and hold light bulb 407. A translucent  
4 material 405 extends along the entire length of the cavity 403 to protect bulbs 407 from  
5 damage and undesirable exposure to weather and other conditions. Translucent  
6 material 405 may have a smooth surface or be textured to accentuate or enhance the  
7 light from bulbs 407. Although only a single cold cathode tube bulb 407 is illustrated, it  
8 should be understood that there may be many bulbs 407 spaced along the length of rib  
9 member 401 to illuminate the area under umbrella apparatus 11, 111, or 211. Rib  
10 member 401 includes a wiring channel 409 configured to receive a wire 411 that  
11 conductively connects all of the bulbs 407 installed in rib member 401, thereby forming  
12 an electrical circuit between bulbs 407 and the rechargeable power source, such as  
13 power sources 50, 150, and 250. In this manner, recessed lighting, which is carried  
14 entirely within rib member 401 and is not otherwise exposed to the elements, is  
15 achieved.

16 A fluid supply channel 421 is provided in order to receive a fluid tight hose which  
17 supplies water to a plurality of misting nozzles 425 which generate mist 427 and 480. A  
18 fluid discharge channel 423 is provided to carry a fluid tight hose which carries water  
19 from the hose in fluid supply channel 421 to misting nozzles 425. In this embodiment,  
20 umbrella apparatus should include a small reservoir (not shown) of water or other water  
21 source, such as an inlet hose, and an electric pump to pressurize and pump the water  
22 through cooling system 410. In this manner, umbrella apparatus 11, 111, or 211  
23 provides both light and a cooling mist to those in close proximity.

24 Referring now to Figure 4C in the drawings, another embodiment of lighting  
25 systems 26, 126, and 226 of the present invention is illustrated. This embodiment is  
26 similar to the embodiment of Figure 4A, with the exception that a different integral  
27 cooling system 510 has been added. In this embodiment, a plurality of lighting  
28 elements 507, preferably cold cathode tube bulbs, are recessed into a rib member 501.  
29 Rib member 501 is indicative of rib members 19, 21, 23, 25, 119, 121, 123, 125, 219,  
30 221, 223, and 225. Cooling system 510 comprises a fanning means that provides a

1 cool breeze under umbrella apparatus 11, 111, or 211. A cavity 503 is formed within rib  
2 member 501. Cavity 503 is adapted to receive and hold light bulb 507. A translucent  
3 material 505 extends along the entire length of the cavity 503 to protect bulbs 507 from  
4 damage and undesirable exposure to weather and other conditions. Translucent  
5 material 505 may have a smooth surface or be textured to accentuate or enhance the  
6 light from bulbs 507. Although only a single cold cathode tube bulb 507 is illustrated, it  
7 should be understood that there may be many bulbs 507 spaced along the length of rib  
8 member 501 to illuminate the area under umbrella apparatus 11, 111, or 211. Rib  
9 member 501 includes a wiring channel 509 configured to receive a wire 511 that  
10 conductively connects all of the bulbs 507 installed in rib member 501, thereby forming  
11 an electrical circuit between bulbs 507 and the rechargeable power source, such as  
12 power sources 50, 150, and 250. In this manner, recessed lighting, which is carried  
13 entirely within rib member 501 and is not otherwise exposed to the elements, is  
14 achieved.

15 A wiring conduit 520 is provided which routes electrical wiring from wire 511 to an  
16 electric motor 524 carried in a recessed cavity 522. Fanning means 528 and 580, such  
17 as fan blades, are carried by rotating shafts 530 which are connected to motors 524.  
18 When energized, motors 524 rotate fan blades 528 and 580, thereby providing a cooling  
19 breeze under umbrella apparatus 11, 111, and 211. A plurality of fan blade sets 528  
20 and 580 may be located at predetermined locations along the length of rib member 501.

21 Referring now to Figure 5A in the drawings, a block diagram representation of  
22 the preferred embodiment of opening and closing systems 40, 140, and 240 is  
23 illustrated. As is shown, a pulley system 600 is coupled through gears 602 to an electric  
24 motor 604. A switch 606 is electrically connected between a power supply 608 and  
25 electric motor 604. Power supply 608 is indicative of rechargeable power systems 50,  
26 150, and 250. External power system charger 610 and solar charger 612 are coupled  
27 to power supply 608 to recharge the rechargeable battery elements. External power  
28 system charger 610 is indicative of external power system chargers 51 and 251. Solar  
29 charger 612 is indicative of alternate power system chargers 62, 162, and 262.  
30 Mechanical actuation of switch 606 allows current to flow from power supply 608 to

1 electric motor 604. Motor 604 works through gears 602 to operate pulley 600, thereby  
2 opening and closing canopy 17, 117, or 217 of umbrella apparatus 11, 111, or 211,  
3 respectively.

4 Referring now to Figure 5B in the drawings, another embodiment of the opening  
5 and closing systems 40, 140, and 240 of the present invention is illustrated. In this  
6 embodiment, a wireless transmitter 708 is utilized to transmit encoded signals and  
7 remotely communicate with a wireless receiver 706 that is carried by umbrella  
8 apparatus 11, 111, or 211, preferably near housings 44, 144, and 244. A decoder 704  
9 is provided to decode the encoded signals. As is conventional with such receivers and  
10 transmitters, transmitter 708 and receiver 706 may be adapted to be coded on a  
11 particular frequency or coding scheme which enable a dedicated transmitter 708 to  
12 actuate a particular receiver 706. A decoder 704 coupled to an electrical switch 702  
13 serves to allow for such identification. Switch 702 controls the application of electrical  
14 energy from a power supply 710 to an electric motor 700. Power supply 710 is indicative  
15 of rechargeable power systems 50, 150, and 250. Motor 700 is indicative of motors 49,  
16 149, and 249. In this manner, a motorized retraction system may be actuated remotely  
17 utilizing wireless transmitter 708.

18 Referring now to Figures 6-9 in the drawings, the preferred embodiments of the  
19 umbrella apparatus of the present invention are illustrated. In these embodiments, the  
20 rechargeable power source and solar recharging system are mounted atop the pole  
21 portion of the umbrella apparatus above the canopy. One concept which runs  
22 throughout the embodiments depicted in Figures 6-9 is the utilization of a "power unit."  
23 This concept involves the placement of a unitary structure at a defined location relative  
24 to the umbrella. For example, in the embodiments of Figures 6-9, the power unit is  
25 shown at a top location directly above the umbrella apparatus, and secured to the pole  
26 portion with a threaded coupling. Figure 6 depicts a top-mounted power unit and a cold  
27 cathode tube lighting system. Figure 7 depicts a top-mounted power unit with a fanning  
28 means cooling system. Figure 8 depicts a top-mounted power unit with mist producing  
29 cooling system. Figure 9 depicts a top-mounted power unit with an automated opening  
30 and closing system.

1           Although Figures 6-9 depict power units with a single electrical system, it should  
2 be understood that in alternative embodiments, one could mix and match these  
3 electrical subassemblies such that a single power unit provides electrical power to two  
4 or more subassemblies. For example, an umbrella apparatus may include a lighting  
5 system and either one or both of the cooling systems described above. Alternatively, an  
6 umbrella apparatus may include a lighting system, a cooling system, and an automated  
7 opening and closing system as described herein. In this manner, the umbrella  
8 apparatus of the present invention is modular such that the different subsystems can be  
9 easily mixed and matched.

10           This modularity allows one to manufacture and sell aftermarket kits which can be  
11 installed and interchanged by the umbrella owners. Such kits may include a power unit  
12 and one or more of the subsystems, such as a lighting system and/or a cooling system  
13 and/or an automated opening and closing system. Because the power unit is relatively  
14 self-contained, little interaction is required to attach the power unit to an umbrella  
15 apparatus. Alternatively, this modularity in design facilitates the mass manufacture of  
16 umbrellas, allowing the electrical system to be manufactured by one factory, and the  
17 umbrella systems, which do not include electrical systems, to be manufactured by a  
18 different factory. The parts can then be brought together in an assembly area and  
19 assembled together.

20           Referring now specifically to Figure 6, an umbrella apparatus 701 is illustrated.  
21 As is shown, a power unit 725 is provided for connection to the uppermost portion of  
22 umbrella apparatus 701. In this embodiment, a cold cathode tube light subassembly  
23 721 is provided for connection at a different location to umbrella apparatus 701. Power  
24 unit 725 includes a solar collector 727 at its uppermost portion. Solar collector 727 is  
25 preferably carried by a top portion 703 of power unit 725. A bottom portion 705 of  
26 power unit 725 defines an interior battery compartment 707. Additionally, power unit  
27 725 carries a coupling mechanism 729 to allow coupling between power unit 725 and a  
28 pole portion 719 of umbrella apparatus 701, pole portion 719 being adapted at an upper  
29 end 711, preferably with threads 713, to releasably receive power unit 725. A top cap  
30 715 hingedly connects pole portion 719 to a canopy 717. Cold cathode tube light

1 subassembly 721 is coupled at a desired location underneath canopy 717 to provide  
2 high intensity light in the area surrounding umbrella apparatus 701. Cold cathode tube  
3 light subassembly 721 is conductively coupled to power unit 725 by wiring 709 that  
4 passes through the hollow interior of pole portion 719. Such light allows users to read,  
5 play games, or perform other leisure activities that require a relatively high intensity  
6 light. The electrical components of umbrella apparatus 701 are entirely independent of  
7 any household electrical system. The power source, such as power sources 50, 150,  
8 and 250, carried by power unit 725 is utilized to energize cold cathode tube light  
9 subassembly 721. During daylight hours, solar energy is collected by solar panel 727  
10 and is converted and utilized to recharge the rechargeable power source which is  
11 maintained within battery compartment 707.

12 Cold cathode tube light subassembly 721 is described below in more detail  
13 below. As will be appreciated by those skilled in the art, other low power lighting  
14 systems may be used instead of cold cathode tube light sub assembly 721. For  
15 example, an LED or fluorescent lighting subassembly may be utilized instead. LED and  
16 fluorescent systems designed for use with solar and low voltage lighting are known in  
17 the art. Such alternative lighting sources may be easily used with the present system in  
18 manners which are recognized by those skilled in the art. Implementation of LED,  
19 fluorescent, or other alternate light sources instead of cold cathode tube light  
20 subassembly 721 is a straightforward and need not be further described in detail.

21 Referring now specifically to Figure 7 in the drawings, an umbrella apparatus 801  
22 is illustrated. As is shown, a power unit 825 is provided for connection to the uppermost  
23 portion of umbrella apparatus 801. In this embodiment, a cooling system 821  
24 comprising a fanning means 831 is provided for connection at a different location to  
25 umbrella apparatus 801. Power unit 825 includes a solar collector 827 at its uppermost  
26 portion. Solar collector 827 is preferably carried by a top portion 803 of power unit 825.  
27 A bottom portion 805 of power unit 825 defines an interior battery compartment 807.  
28 Additionally, power unit 825 carries a coupling mechanism 829 to allow coupling  
29 between power unit 825 and a pole portion 819 of umbrella apparatus 801, pole portion  
30 819 being adapted at an upper end 811, preferably with threads 813, to releasably

1 receive power unit 825. A top cap 815 hingedly connects pole portion 819 to a canopy  
2 817. Cooling system 821 is coupled at a desired location underneath canopy 817 to  
3 provide a cooling breeze in the area surrounding umbrella apparatus 801. Cooling  
4 system 821 is conductively coupled to power unit 825 by wiring 809 that passes through  
5 the hollow interior of pole portion 819. The electrical components of umbrella apparatus  
6 801 are entirely independent of any household electrical system. The power source,  
7 such as power sources 50, 150, and 250, carried by power unit 825 is utilized to  
8 energize cooling system 821. During daylight hours, solar energy is collected by solar  
9 panel 827 and is converted and utilized to recharge the rechargeable power source  
10 which is maintained within battery compartment 807.

11 Referring now specifically to Figure 8 in the drawings, an umbrella apparatus 901  
12 is illustrated. As is shown, a power unit 955 is provided for connection to the uppermost  
13 portion of umbrella apparatus 901. In this embodiment, a cooling system 921  
14 comprising a misting system 931 is provided for connection at a different location to  
15 umbrella apparatus 901. Power unit 955 includes a solar collector 957 at its uppermost  
16 portion. Solar collector 957 is preferably carried by a top portion 903 of power unit 955.  
17 A bottom portion 905 of power unit 955 defines an interior battery compartment 907.  
18 Additionally, power unit 955 carries a coupling mechanism 959 to allow coupling  
19 between power unit 955 and a pole portion 919 of umbrella apparatus 901, pole portion  
20 919 being adapted at an upper end 911, preferably with threads 913, to releasably  
21 receive power unit 955. A top cap 915 hingedly connects pole portion 919 to a canopy  
22 917. The electrical components of umbrella apparatus 901 are entirely independent of  
23 any household electrical system. The power source, such as power sources 50, 150,  
24 and 250, carried by power unit 955 is utilized to energize cooling system 921. During  
25 daylight hours, solar energy is collected by solar panel 957 and is converted and utilized  
26 to recharge the rechargeable power source which is maintained within battery  
27 compartment 907.

28 Cooling system 921 is coupled at a desired location underneath canopy 917 to  
29 provide a cooling mist in the area surrounding umbrella apparatus 901. Cooling system  
30 921 is conductively coupled to power unit 955 by wiring 909 that passes through the

1 hollow interior of pole portion 919. Cooling system 921 is a misting system comprising  
2 a reservoir 925, or other water source, a pump 927, water feed lines 929, and mist  
3 nozzles 923. Pump 927 pressurizes and pumps the water from reservoir 925 through  
4 water feed lines 929 and out of mist nozzles 923, which are located at selected spaced  
5 intervals under canopy 917, at a selected flow rate. Reservoir 925 may be a  
6 conventional ice cooler, such that the mist is chilled water.

7 Referring now specifically to Figure 9 in the drawings, an umbrella apparatus  
8 1001 is illustrated. As is shown, a power unit 1055 is utilized to provide electrical power  
9 to an automated opening and closing system 1050. Power unit 1055 includes a solar  
10 collector 1027 at its uppermost portion. Solar collector 1027 is preferably carried by a  
11 top portion 1003 of power unit 1055. A bottom portion 1005 of power unit 1055 defines  
12 an interior battery compartment 1007. Additionally, power unit 1055 carries a coupling  
13 mechanism 1029 to allow coupling between power unit 1055 and a pole portion 1019 of  
14 umbrella apparatus 1001, pole portion 1019 being adapted at an upper end 1011,  
15 preferably with threads 1013, to releasably receive power unit 1055. A top cap 1015  
16 hingedly connects pole portion 1019 to a canopy 1017. The electrical components of  
17 umbrella apparatus 1001 are entirely independent of any household electrical system.  
18 Automated opening and closing system 1050 is conductively coupled to power unit 1055  
19 by wiring 1009 that passes through the hollow interior of pole portion 1019. The power  
20 source, such as power sources 50, 150, and 250, carried by power unit 1055 is utilized  
21 to energize automated opening and closing system 1050. During daylight hours, solar  
22 energy is collected by solar panel 1027 and is converted and utilized to recharge the  
23 rechargeable power source which is maintained within battery compartment 1007.

24 Automated opening and closing system 1050 is carried at the uppermost portion  
25 of pole portion 1019. Opening and closing system 1050 includes a motor 1021, a  
26 transmission 1023, a line winding shaft 1025, a pulley system 1031, and a cable system  
27 1033. These components cooperate to open and close the umbrella in response to the  
28 receipt of a command signal. The command signal may be supplied by the actuation of  
29 a switch (see Figures 1-3) carried on pole portion 1019, or it may be a wireless signal  
30 received from a paired transmitter receiver system (see Figure 5B).



1 Referring now to Figure 10 in the drawings, a schematic of the cold cathode tube  
2 lighting system of the present invention is illustrated. The invention is to utilize in  
3 combination a cold cathode lamp, a power inverter which supplies alternating current to the  
4 cold cathode lamp, a rechargeable DC battery pack, and a solar collector. This is depicted  
5 in simplified form in Figure 10. This may be utilized in any outdoor application in which  
6 there is no easy or convenient access to household power. The system is entirely self-  
7 contained and does not require any household power for operation, or charging. As is  
8 shown, the cold cathode tube lighting system 3000 includes a cold cathode lamp 3001 that  
9 is supplied with AC power from a power inverter 3007. A DC battery pack 3003 includes  
10 rechargeable batteries that supply DC current to power inverter 3007. A solar collector  
11 3005 is provided to recharge the batteries contained within DC power pack 3003.

12 A cold cathode tube is a lamp that produces light by the passage of an electric  
13 current through a vapor or gas maintained within a tube. A cold cathode tube does not  
14 require any heating above ambient temperature to produce light. The tube is phosphor  
15 coated on its inner surface, and thus may emit various colored light. In most cases, cold  
16 cathode tube lamps are low-pressure mercury vapor lamps. Such lamps use a 253.7  
17 nanometer ultraviolet emission from mercury vapor excited by an electrical discharge  
18 through the lamp to charge the phosphors maintained on the wall of the lamp.

19 The optimum operating temperature for cold cathode tube is approximately 40  
20 degrees Celsius, although Applicant believes that these lamps can be produced in a  
21 manner to reliably provide outdoor lighting in temperatures as cold as 15 degrees  
22 Fahrenheit. While the cold cathode tube does not require heating, the output of the lamp  
23 does vary based upon the ambient temperature. At room temperature, the initial output of  
24 a lamp is only about seventy percent of its steady state value at 40 degrees Celsius. In  
25 contrast, its output is only 25 percent when the lamp is started at zero degrees Celsius.  
26 Cold starts do require additional voltage from the power source to ensure reliable  
27 operation. However, the number of lamp "starts" has no adverse effect on the lamp. This  
28 is not true for fluorescent lamps, which degrade over time due to the number of "starts."  
29 Cold cathode tubes may be utilized to supply a white light output.

1 In the preferred embodiment, a cold cathode tube manufactured by Nanjing Lampus  
2 Electronics Company, Ltd. is utilized. Specifically, a lamp type CFL-20 is utilized. This has  
3 an inner diameter of 1.5 millimeters. The tube length is variable, and may be anywhere in  
4 the range of 50 millimeters to 30 millimeters in overall length. The tube is adapted to  
5 operate on four milliamps of tube current. The tube voltage is in the range of 200 to 750  
6 Volts. The average brightness of this particular tube is 40,000 cd/m<sup>2</sup>.

7 Another advantage of cold cathode tubes is that the tubes can be very thin in  
8 diameter. For example, in the preferred implementation, the cold cathode tube may be one  
9 or two millimeters in diameter. A cold cathode tube can be bent into any shape and can be  
10 formed in very long lengths, such as several feet long. Thus, cold cathode tubes provide  
11 greater light output per foot versus conventional lighting.

12 Another significant advantage of cold cathode tubes is that they have relatively long  
13 lamp life. It is not unusual to have lamp lives which are thirty to forty thousand hours of  
14 use. In other words, these cold cathode tubes have, for all practical purposes, an infinite  
15 life span.

16 They are low power devices. They do not generate a lot of heat. They provide high  
17 lumen output. For these reasons, fewer batteries are needed to drive the cold cathode ray  
18 tube, and smaller solar cell panels may be utilized to recharge the batteries. In other  
19 words, relatively small form factors can be achieved because the solar cells, the batteries,  
20 and the bulbs can be relatively small in size.

21 The present invention can be implemented on a small, medium, or large scale so  
22 the solar cell panels and batteries may be moved up in size to either provide greater light  
23 output or to provide for a longer useful life.

24 Additionally, the present invention may be considered to satisfy three separate and  
25 distinct outdoor lighting applications, all of which may be incorporated into the umbrella  
26 apparatus of the present invention.

27 The first application is that of a "special purpose light," or "task light," such as for  
28 security applications. These special purpose lights would provide very light output, for a

1 relatively short duration. One example would be the utilization of the cold cathode ray tube  
2 to provide extremely high light output for a very small area for a very short time, all in  
3 response to detection of motion in a particular area. For example, a system can be  
4 configured to detect motion in a doorway, motion in a yard, motion in a driveway, or the  
5 like. The brightness can be provided which can be far in excess of  $40,000 \text{ cd/m}^2$ . For  
6 example,  $100,000$  to  $200,000 \text{ cd/m}^2$  may be provided for a very small area for a very short  
7 duration. For example, the duration may be a few minutes to ten minutes.

8 The second application requires a medium amount of light output, but requires  
9 longer periods of operation or wider areas of coverage. For example, the light assembly  
10 provided with the umbrella provides a relatively high light output, such as in the range of  
11  $20,000$  to  $100,000 \text{ cd/m}^2$ , in order to allow one to read, play games, operate a computer, or  
12 do needlework under the umbrella. Preferably, the battery pack and associated solar panel  
13 is sufficient to allow the system to operate continuously for a time interval in the range of 8-  
14 12 hours. Additionally, and preferably, the solar panel should be of the size and output  
15 which is sufficient to fully recharge the battery pack during the daylight hours.

16 A third application requires a lower level of light intensity. A good example would be  
17 lawn, patio, walkway, or landscape lighting. One does not ordinarily expect to be able to  
18 read or do intricate work under this type of lighting. In contrast, all that is expected is that a  
19 reasonable amount of light be provided to allow one to walk safely through an area. This  
20 type of task may require brightness in the range of  $6,000 \text{ cd/m}^2$  to  $60,000 \text{ cd/m}^2$ .

21 Referring now to Figure 11 in the drawings, a block diagram representation of the  
22 application of the present invention to a lawn lighting scenario is illustrated. In this  
23 scenario, a plurality of solar panels 4001, 4003, 4005, and 4007 are connected together in  
24 series. Preferably, solar panels 4001, 4003, 4005, and 4007 are manufactured by  
25 Siemens and comprise mono-crystal solar panels, each providing 1.5 Volts. The total  
26 current for the array of solar panels is about 80 milliamps. The current from solar panels  
27 4001, 4003, 4005, and 4007 is passed through a diode 4009 and then to a battery pack  
28 4011. Battery pack 4011 includes a plurality of batteries 4013, 4015, and 4017, for  
29 example three AA batteries. In alternative embodiments, as few as two batteries may be

1 used. As is shown, each battery is a 1.2 Volt Nickel Cadmium battery. They collectively  
2 provide 700 milliamp hours of power.

3 The output of DC battery pack 4011 is provided as an input to an inverter 4019.  
4 Inverter 4019 receives 4.8 Volts DC in and produces as an output of 800 Volts rms AC at  
5 40 Hertz. The total current of the output is 4-6 milliamps.

6 This is provided to the cathode of a cold cathode ray tube lamp 4021. The current  
7 passes through the vapor maintained within cold cathode ray tube lamp 4021 and causes  
8 electrons to be stripped from the gas. These electrons collide with the phosphorus coating  
9 on the interior surface of cold cathode ray tube lamp 4021, thereby emitting light.

10 Although the invention has been described with reference to a particular  
11 embodiment, this description is not meant to be construed in a limiting sense. Various  
12 modifications of the disclosed embodiments as well as alternative embodiments of the  
13 invention will become apparent to persons skilled in the art upon reference to the  
14 description of the invention. It is therefore contemplated that the appended claims will  
15 cover any such modifications or embodiments that fall within the scope of the invention.